



Technical Data

Document Reference
Data Sheet

R15100UE

RAMCRO - BMS-PVC-BC-UnScreened Cable For standard applications, flame retardant.

Multicore, PP-Insulation, UnScreened, PVC-Sheath

SSS0201HBAXH-RB-CH

Application

PVC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.

Construction

		Unit	Nominal Value
Formation	2 Cores		
Section	14 AWG		
Conductor	Plain annealed copper wire, Multistrand	mm	1,8
Insulation	Polypropylene - PP	mm	2,3
Colour Code	Black, Red		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Polyvinyl chloride - PVC - Grey RAL 7001	mm	5,5
Cable Printing	RAMCRO ITALY R15100UE - 2C 14AWG UNSHIELDED AUDIO, CONTROL&INSTRUMENTATION CABLE PVC 300V 75C IEC 60332-1/UL 1581- SSS0201HBAXH-RB-CH-"PROD.WEEK/21+BATCH+METER MARKING		

Technical Data & Standard References

Fire Propagation:		Type of Cable:	BMS-PVC-BC-UnScreened Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Limiting Oxygen Index (LOI)	(min 30%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 15%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

Electrical & Mechanical Data

Conductor Cross-section	Nom.	14 AWG	Temperature Range:			
DC Resistance per core at 20° C	max	Ω/km	9,36		During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	1000		During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max	pF/m	51			
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter	
Test Voltage - Core/Core	V	2000	Max Pulling Tension	N/mm2	193	
Test Voltage - Core/Screen	V	N.A.	Weight Approx	kg/km	56	
Operating Voltage	V	300	Put up length	mt	305	

Issued by: RAMCRO S.p.A.

Prepared by RAMCRO Tech

Creator: LDG

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

Transfer to third parties only under authorization by Ramcro S.p.A.

Printing errors excepted. Subject to alterations.



Date of issue:

09/12/2019 00:00

Empty Form